

# MSQ-CC-LRE V2

MotionSeQuencer for ControlChanges

for 2xLRE8x2 Boards

for 1x LRE5-LCD2 Boards

Synth-Patch-Editor & Motion-Sequencer 4 ControlChange (= CC-Automation)

## Introduction

Controls and automate a Nord Drum2 (Drum-Synth )[NORD DRUM 2](#)

### It acts as:

- **Midi Merger** NTE,CLK,PC merge with CC... - **Patch Manager** it replaces the Synths internal Patch Storage, each PC Number from your Sequencer is added by the BANK CC (CC 32), where each Nr is ADD 128 PC Numbers more...
- **Motion Sequencer** Record your Controller Movements in a Sequence in 32th Resultion @ maximal 256 Steps length

## Features

- **Remote your Synths** by: 8x Midichannels with up to 32x Control Change (CC)
  - **Save the Patches** and dump it to Synth
  - **Load hundrets of Patches** via received Program Change + the Bank-CC (CC32)
  - **Save Patches** vie CC24 + CC value 0-127... when sending before a BankCC32 you can expand that to 128x128 patches
  - **Record CC-Motion-Sequences - PLAY Motions-Sequences** up to 256 steps @ 32th rate -
  - **VELOCITY MORPH** Add Velocity-Ammount to CCs
  - **MERGE** incoming Midi-Notes/Clock/Pitchbend with Automated CCs
  - **Set Sequencer Beatstructure** - how to interpret Clock-ticks (4/4, 5/4, 6/4, 7/4...) - CC23
  - **Global Page:** for example you use 8 simular Drum-Voices, with the Global you have 8 channel strips with dedicated Controlls, for example:  
8xVolume, 8xTone/Noise-Mix, 8xDistortion, 8xClick
- if you have one Synth over 2xMSQ\_CC\_LRE Tracks(booth set to MidiChannel 0, to get 64CCs instead of 32), then the Global Page: have the ability to show/edit a parameter from Track1Voice on Track1Global, and from Track2Voice on Track2Global... it depends how you set the Midichannel in the Systemsettings (which are hardcoded but via Mapping Array changeable)
- for one multipart-synth, MSQ\_CC\_LRE do all the Preset Store, and Automations, so it is one Unit > to use the Unit in a other way would make all the Patches (128x128 patches) useless, so once done, its bound to it, load all with Programchange! minimal is better here, there will be other **MSQs** outthere see [MSQ-CC-BCR](#)


# Hardware Requirements

## External Requirement:(for example)


- Melody/Clock Source with ProgramChange-Output: [midibox\\_seq\\_v4](#)! oops that dont do PC...
- Melody/Clock Destination: NordDrum 2

## Midibox:

- 1x [core32](#)



- 1x [LRE5-LCD2](#)
- 2x [mb-lre8x2cs\\_pcb](#)
- 8x [LRE-OLED-Bar](#)



- 17x SSD1306 OLED Screens (smalles variant, 7 Pin)
- 1x DINX4
- 1x 1xMidi IO or 1x Euro-Midi-IO
- SD-Card, formatted with FAT32
- Soldering Iron, Wires, PCB....
- USB Power Supply


## Setting

### Cabeling MIDI

MidiiO PortB Out >> Synth Midi IN

MidiiO PortB In >> Clock+Notes

### Cabeling Modules



## Frontpanels

### MBHP

see [LRE-OLED-Bar](#)



## To Do

Since we have 18 Screens, write the code for it - special the labeling > Sys  
Make a System Menue to set CC NRs on the fly...

maybe scale min max values for CC: for example different synths have only 0-3value instead of 0-127, by different functions like WAVEFORM...) - this will be interesting when using other synths then nord drum...

## Resources

# Community users working on it

- **Phatline** = Programming, Documentation...

Just let a Private message on the forum to user already involved, the sourcecode is included in the firmware .zip!!!

From:  
<http://midibox.org/dokuwiki/> - **MIDIbox**

Permanent link:  
<http://midibox.org/dokuwiki/doku.php?id=msq-cc-lre-v2&rev=1643334241>

Last update: **2022/01/28 01:44**

